

**SAFETY DATA SHEET**According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision date: 11/23/2021**Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking**

**Product Name:** Con-Patch II **PART A**  
**Product Codes:** Series No. 8145-10  
**Recommended Use:** Filler/Patch  
**Sold By:** Gabriel First Corp.  
**Street Address:** PO Box 191  
**City, State, Zip:** East Rochester, NY 14445-0191  
**Telephone:** 585-381-7000  
**Emergency Phone:** 800-424-9300

**Chemical Name or Class:** Epoxy Mixture

**Section 2 – Hazards Identification****Hazard Overview****GHS Classification:**

Serious eye damage/Eye irritation: Category 2A  
Skin irritation: Category 2  
Skin sensitizer: Category 1  
Long term hazards to aquatic environment: Category 2

**GHS Label Elements and Precautionary Statements****Label Elements:****Hazard Statements:**

**Warning:** Causes serious eye irritation.  
**Warning:** Causes skin irritation.  
**Warning:** May cause an allergic skin reaction.  
Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**

P102 Keep out of reach of children.  
P103 Read label before use.  
P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.

**Response:**

P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 IF eye irritation persists: Get medical advice/attention.  
P391 Collect spillage.  
P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**Other Non-Classifiable Potential Hazards**

**Carcinogen:** Category 2

**HMIS Hazard Classification**

**Health: 1**      **Flammability: 1**      **Reactivity: 0**      **Personal Protective Equipment: B**

**Potential Health Effects**

**Eyes:** May cause irritation but no corneal injury is likely.  
**Skin:** May cause irritation or allergic skin response.  
**Ingestion:** This material has a probable low acute oral toxicity.  
**Inhalation:** No guide for control known, however, exposure to heated vapors can cause irritation to the nose, throat or mucous membranes.  
**Health Hazards (Acute and Chronic):** Epoxy resins can cause sensitization by exposure through contact or high concentration of vapor.  
**Eyes:** Injury is unlikely but stain for evidence of corneal injury.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Medical Conditions Generally Aggravated By Exposure:

Respiratory conditions or other allergic ailments.

### Carcinogenicity:

OSHA: No

NTP: Yes

IARC: Yes

### Additional Carcinogenicity Information:

Some colors may contain carbon black - Explanation of Carcinogenicity for carbon: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

## Section 3 – Composition/Information on Ingredients

Ingredient	CAS No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	None	None	None	60-100
Alkyl Glycidyl Ether	68609-97-2	None	None	None	10-30
Epichlorhydrin-Polyglycol Reaction Products	26142-30-3	None	None	None	3-7
Colors May Contain @ 3-7%:					
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3	
*Carbon	1333-86-4	3.5ppm	3.4ppm	None	<1.0
Precipitated Silica	112926-00-8	None	80mg/m3	None	
Iron III Oxide	1309-37-1	10mg/m3	5mg/m3	None	
Yellow Pigment	Not Available	None	None	None	
Zinc Sulfide (Component of Yellow Pigment)	1314-98-3	None	None	None	
Barium Sulfate (component of yellow pigment)	7727-43-7	None	None	None	
Titanium Dioxide (component of yellow pigment)	13463-67-7	None	None	None	
Pigment Yellow 65 (component of yellow pigment)	6528-34-3	None	None	None	
Iron III Hydroxide	20344-49-4	15mg/m3	5mg/m3	None	
C.I. Pigment Blue	147-14-8	1mg/m3	1mg/m3	None	
Aluminum Oxide	1344-28-1	15mg/m3	10mg/m3	None	
Silica, Amorphous	7631-86-9	80mg/m3	10mg/m3	None	
Iron Oxide Yellow	51274-00-1	15mg/m3	10mg/m3	None	
Silica, Amorphous	7631-86-9	80mg/m3	10mg/m3	None	

**SECTION 3 NOTES:** \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

## Section 4 – First Aid Measures

<b>Eyes:</b>	Flush eyes with water for at least fifteen minutes and consult a physician.
<b>Skin:</b>	Skin contact will normally cause no more than irritation but wash affected area with soap and water and remove contaminated clothing promptly.
<b>Ingestion:</b>	Low in toxicity, induce vomiting only if large amounts of material are ingested, and otherwise do Not induce vomiting. In either case consult with a physician.
<b>Inhalation:</b>	Remove victim to fresh air and administer oxygen if necessary.
<b>Notes to physicians or First Aid providers:</b>	

## Section 5 – Firefighting Measures

<b>Flammable Limits in Air, (% by volume)</b>	<b>Upper:</b> Not available <b>Lower:</b> Not available
<b>Flash Point:</b> 200+F <b>Method Used:</b> Seta flash	
<b>Extinguishing Media:</b>	Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog.
<b>Special Fire Fighting Procedures:</b>	Do not enter confined area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Cool all fire exposed containers with water.
<b>Unusual Fire and Explosion Hazards:</b>	None known.

## Section 6 – Accidental Release Measures

<b>Steps To Be Taken In Case Material Is Released or Spilled:</b>	Wear respirator and protective clothing. Shut off the source at the leak. Remove excess with vacuum truck and take up the remainder with an absorbent such as clay and place in disposal containers. Flush area with water to remove residue.
---	---

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Section 7 – Handling and Storage

#### Precautions To Be Taken In Handling and Storage:

Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the SDS's of all the components prior to using material. Properly label all containers.

#### Other Precautions:

Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles cannot be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof.

### Section 8 – Exposure Controls/Personal Protection

#### Respiratory Protection:

Use a NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134. General exhaust is usually sufficient in lieu of NIOSH respirator.

#### Ventilation:

General exhaust is usually sufficient to control vapors and exposure hazards.

#### Protective Gloves:

Impervious gloves – neoprene or rubber.

#### Eye Protection:

Splash goggles or glasses with side shields.

#### Other Protective Clothing or Equipment:

Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

#### Work Hygienic Practices:

Observe good general hygienic practices.

See Section Three for occupational exposure limit values.

### Section 9 – Physical and Chemical Properties

#### Appearance And Odor:

Medium viscosity liquid in varying colors or clear.

#### Boiling Point or Range:

200 to 279F

#### Vapor Density (air = 1):

N/A

#### Specific Gravity (H<sub>2</sub>O = 1):

1.1

#### Evaporation Rate:

N/A

#### Solubility in Water:

Negligible

#### Odor Threshold:

N/A

#### pH:

N/A

#### Melting Point/Freezing Point:

N/A

#### Vapor Pressure:

N/A

#### Auto-ignition Temperature:

N/A

#### Partition Coefficient: n-Octanol/Water:

N/A

#### Decomposition Temperature:

N/A

### Section 10 – Stability and Reactivity

#### Stability:

Stable

#### Conditions to Avoid (Stability):

Avoid excessive heat or open flames.

#### Incompatibility (Material to Avoid):

Can react vigorously with strong oxidizing agents and strong Lewis acids or mineral acids.

#### Hazardous Decomposition or By-Products:

CO<sub>2</sub>, Aldehydes, Acids. Reaction with some curing agents can generate large amounts of heat.

#### Hazardous Polymerization:

Will not occur.

### Section 11 – Toxicological Information

No data for the product itself.

#### Component Data:

##### Component CAS# 25068-38-6:

Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD<sub>50</sub> >5000 mg/kg (rat), Dermal LD<sub>50</sub> >6000 mg/kg (rabbit).

##### Component CAS# 68609-97-2:

Possible sensitizer, eye and skin irritant, Oral LD<sub>50</sub> >10000 mg/kg (rat), Inhalation LD<sub>50</sub> – no microscopic changes.

##### Component CAS# 26142-30-6:

SKIN: The LD<sub>50</sub> for skin absorption in rats is >2000 mg/kg, INGESTION: The oral LD<sub>50</sub> for male rats is >4000 mg/kg;

##### Component Titanium Dioxide:

INHALATION 4 h LC<sub>50</sub> > 6.82 mg/l; Oral LD<sub>50</sub> > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Component Carbon:

IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg

### Component CAS# 112926-00-8:

LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

### Component Iron III Oxide CAS# 1309-37-1:

Acute Oral Toxicity LD50 >5000 mg/kg (rat). Acute Dermal Toxicity LD50 >5000 mg/kg (rat)

### Component Yellow Pigment:

Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200. Acute oral value of 20 gm/kg or greater in rats.

### Component Iron III hydroxide CAS# 20344-49-4:

Acute Oral Toxicity LD50 >5000 mg/kg (rat).

### Component CAS# 2210-79-9:

Acute Health Hazard - Ingestion : LD50 : 5,800 mg/kg Species : Rat. Inhalation: LC50 (4 h) : 1220 ppm Species : Rat. Skin : LD50 : > 2,000 mg/kg Species : Rabbit. Method : Estimated. Eye irritation/corrosion: Mild eye irritation. Acute dermal irritation/corrosion : Severe skin irritation. Sensitization : May cause sensitization by skin contact.

## Section 12 – Ecological Information

No data for the product itself.

### Component Data:

#### Component CAS# 25068-38-6:

Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

#### Component CAS# 26142-30-6:

DEGRADATION & PERSISTENCE: Based on the stringent test guide lines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions. Biodegradation reached in CO<sub>2</sub> Evolution Test (Modified Sturm Test, OECD Test No. 301B) after 28 day: 14-21%.

ECOTOXICITY: Material is practically non-toxic to fish on an acute basis.

(LC50 greater than 100 mg/L). Material is practically non-toxic to aquatic invertebrates on an acute basis (LC50 greater than 100 mg/L).

#### Component Titanium Dioxide:

Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

#### Component CAS# 112926-00-8:

Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l

#### Component Iron III oxide CAS# 1309-37-1

Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Acute toxicity to Aquatic Invertebrates EC0 > 10000 mg/l (water flea). Toxicity to Microorganisms EC0 > 1000mg/l (pseudomonas putida)

#### Component Yellow Pigment:

Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

#### Component Iron III hydroxide CAS# 20344-49-4:

Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Toxicity to Microorganisms EC0 > 10000mg/l (pseudomonas putida)

## Section 13 – Disposal Considerations

### Waste Disposal Method:

Dispose of the material in a waste disposal site in accordance with local, state, and federal law.

## Section 14 – Transport Information

### DOT:

Not regulated

### IMO/IMDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS BISPHENOL A DIGLYCIDYL ETHER POLYMER), 9, PGIII, MARINE POLLUTANT

## Section 15 – Regulatory Information

No data for the product itself.

### Component Data:

#### Component CAS# 25068-38-6:

Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;.

#### Component CAS# 68609-97-2:

Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Component CAS# 26142-30-6:

Component is on TSCA, Canada DSL, EINECS, AICS, ENCS, PICCS and SEPA inventory lists.

### Component Titanium Dioxide:

Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List. Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

### Component Carbon:

Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada

### Component CAS# 112926-00-8:

Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,

### Component Iron III Oxide CAS# 1309-37-1

Listed on TSCA Inventory. Section 313/312 hazard category: Chronic Health Hazard. Potential exposure to all of the California Proposition 65 have been determined to be below the No Significant Risk Level (NSRL). Component and its impurities (1%) are on the Pennsylvania, New Jersey Right To Know substance lists. Component contains the following chemicals listed on the New Jersey and Pennsylvania RTK Special Hazardous Substance lists: Manganese CAS# 7439-96-5 (0.7%) and Aluminum CAS# 7429-90-5 (0.29%). Component contains the following ingredients which are on the Pennsylvania, Massachusetts Hazardous Substance Lists: Chromium CAS# 7440-47-3 (0.075%) and Nickel CAS# 7440-02-0 (0.04%) Component contains the following chemicals on the California Proposition 65 List known to the State of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.04%) and Cobalt CAS# 7440-48-4 (30 ppm).

### Component Yellow Pigment:

Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

### Component Iron III hydroxide CAS# 20344-49-4:

Listed on TSCA Inventory. Potential exposure to all of the California Proposition 65 Chemicals have been determined to be below the No Significant Risk Level (NSRL). Components are on the Pennsylvania Right To Know Substance List. Component contains the following chemicals listed on the Pennsylvania RTK Special Hazardous Substance Lists: Chromium CAS# 7440-47-3 (0.02%) and Nickel CAS# 7440-02-0 (0.015%). Component contains the following ingredients which are on the Massachusetts Hazardous Substance Lists: Chromium CAS# 7440-47-3 (0.02%), Arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Nickel CAS# 7440-02-0 (0.015%) Component contains the following chemicals on the California Proposition 65 List known to the State of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), Arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70ppm).

### Component CAS# 147-14-8:

Component is on the TSCA List. and not controlled under WHMIS. Component is a CERCLA hazardous substance

### Component CAS# 1344-28-1:

Component is on the Massachusetts, New Jersey, Pennsylvania Right To Know lists. Component is on TSCA list and Canada DSL.

### Component CAS# 7631-86-9:

Component is on the Minnesota Right To Know list. Component is on TSCA list and Canada DSL.

### Component CAS# 51274-00-1:

Component is on the TSCA list and Canada DSL.

### Component CAS# 7631-86-9:

Component is on the Minnesota Right To Know list. Component is on TSCA list and Canada DSL.

## Section 16 – Other Information

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**Revision Date: 11/23/2021**

## Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

**Product Name:** Con-Patch II **PART B**  
**Product Codes:** Series No. 8145-10  
**Recommended Use:** Filler/Patch  
**Sold By:** Gabriel First Corp.  
**Street Address:** PO Box 191  
**City, State, Zip:** East Rochester, NY 14445-0191  
**Telephone:** 585-381-7000  
**Emergency Phone:** 800-424-9300  
**Date Revised:** 11/23/2021  
**Chemical Name or Class:** Polyamine Mixture

## Section 2 – Hazards Identification

### Hazard Overview

#### GHS Classification:

Specific target organ toxicity single exposure:	Category 3	Skin sensitizer :	Category 1B
Acute oral toxicity:	Category 4	Skin corrosion/irritation:	Category 1
Acute dermal toxicity:	Category 4	Reproductive toxicity:	Category 2
Serious eye irritation/damage:	Category 1	Acute hazard to aquatic environment:	Category 2

#### GHS Label Elements and Precautionary Statements:

##### Label Elements:



##### Hazard Statements:

**Warning:** May cause respiratory irritation.  
**Warning:** Harmful if swallowed.  
**Warning:** Harmful in contact with skin.  
**Danger:** Causes serious eye damage.  
**Warning:** May cause an allergic skin reaction.  
**Danger:** Causes severe skin burns and eye damage.  
**Warning:** Suspected of damaging fertility of the unborn child.  
**Warning:** Toxic to aquatic life.

##### Precautionary Statements:

P102 Keep out of reach of children.  
 P103 Read label before use.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P264 Wash hands thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P264 Wash hands thoroughly after handling.  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P273 Avoid release to the environment.

##### Response:

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.  
 P330 Rinse mouth.  
 P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P361+P364 Take off immediately all contaminated clothing and wash it before reuse.  
 P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 If in eyes, immediately call a POISON CENTER or doctor/physician.  
 P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.



## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Section 6 – Accidental Release Measures

**Steps To Be Taken In Case Material Is Released or Spilled:**

Avoid contact with material. Wear the appropriate safety equipment. Stop spill at source, dyke area to prevent spreading. Pump liquid to salvage tank. Take up remainder with clay or other absorbent and place in disposal containers.

### Section 7 – Handling and Storage

**Precautions To Be Taken In Handling and Storage:**

Avoid all skin contact. Avoid breathing vapors. Reseal partially used containers. Properly label all containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices.

**Other Precautions:**

Mixed materials contain the hazards of all the components, therefore, read the SDS of all components to become familiar with all hazards prior to using this product.

### Section 8 – Exposure Controls/Personal Protection

**Respiratory Protection:**

NIOSH approved respirator protection required in the absence of proper environmental controls. For emergencies a self-contained breathing apparatus or a full face respirator is recommended.

**Ventilation:**

Avoid breathing vapors. Ventilation must be sufficient to control vapors.

**Protective Gloves:**

Impervious gloves – neoprene or rubber.

**Eye Protection:**

Splash goggles or glasses with side shields.

**Other Protective Clothing or Equipment:**

Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

**Work Hygienic Practices:**

Observe good general hygienic practices.

See Section Three for occupational exposure limit values.

### Section 9 – Physical and Chemical Properties

<b>Appearance and Odor:</b>	Amber clear liquid with amine odor.
<b>Boiling Point or Range:</b>	155 to 401 Deg F
<b>Vapor Density (Air = 1):</b>	N/A
<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	1.1
<b>Evaporation Rate:</b>	N/A
<b>Solubility in Water:</b>	Negligible

<b>Odor Threshold:</b>	N/A
<b>pH:</b>	N/A
<b>Melting Point/Freezing Point:</b>	N/A
<b>Vapor Pressure:</b>	N/A
<b>Auto-ignition Temperature:</b>	N/A
<b>Partition Coefficient: n-Octanol/Water:</b>	N/A
<b>Decomposition Temperature:</b>	N/A

### Section 10 – Stability and Reactivity

<b>Stability:</b>	Stable
<b>Conditions to Avoid (Stability):</b>	Avoid excessive heat or open flames.
<b>Incompatibility (Material to Avoid):</b>	Can react vigorously with strong oxidizing agents and strong Lewis acids or mineral acids.
<b>Hazardous Decomposition or By-Products:</b>	CO <sub>2</sub> , aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.
<b>Hazardous Polymerization:</b>	Will not occur

### Section 11 – Toxicological Information

No data for the product itself.

**Component Data:**

**Component CAS# 694-83-7:**

LD50 = 2,300 mg/kg (species rat) May cause sensitization by contact or inhalation.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Component Benzyl Alcohol:

Inhalation LC50 (4hr) >4178 mg/l (rat),  
 Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No Observed Adverse Effect Level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

### Component CAS# 69-72-7:

Acute Oral Toxicity LD50 (rat) = 891 mg/kg (behavioral somnolence (general depressed activity, Behavioral muscle weakness).  
 Acute Inhalation LC50 (rat) >900 mg/m<sup>3</sup>, 1 hr.  
 Acute Dermal LD50 (rabbit) >10,000 mg/kg. Skin Irritation (rabbit) – mild skin irritation -24hr.  
 Eye Irritation (rabbit) – severe eye irritation.

### Component CAS# 111-40-0:

Inhalation: LC50 (4hr) <0.3 mg/l (rat); Skin: LD50 >5000 mg/kg (rabbit). Ingestion: LD50 2960 mg/kg (rat). Severe Eye irritation, Moderate skin irritation, may cause sensitization by skin contact or inhalation.

### Component CAS# 80-05-7:

Ingestion LD50 Oral (rat) = 3250 mg/kg. Irritation Data Skin (rabbit) 500 mg/24 hr (mild irritation effects. Irritation data eyes (rabbit) 0.25mg/24 hr (severe irritation effect). Skin contact or inhalation may cause sensitization. Component may impair fertility based on toxicology of similar products.

### Component CAS# 140-31-8:

Draize test, rabbit, eye: 20 mg/24H Moderate; Draize test, rabbit, skin: 5 mg/24H Severe; Oral, rat: LD50 = 2140 ul/kg;  
 Skin, rabbit: LD50 = 880 ul/kg; Carcinogenicity: Not listed by ACGIH, IARC, NTP, or CA Prop 65. May cause Sensitization by skin contact.

### Component Nonyl Phenol:

Median Lethal Dose Oral: LD50 0.58g/kg (rat) moderately toxic. Dermal LD50 2.14g/kg (rabbit) slightly toxic. Skin Draize Test, rabbit,: 500 mg/m<sup>3</sup> 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

### Component CAS# 90-72-2 and CAS# 71074-89-0:

Oral LD50 (rat) 1200 mg/kg; Dermal LD50 (rabbit) 1280 mg/kg; Inhalation LC50 (rat) > 0.5 mg/liter/1 hour; Severe irritant to eyes of a rabbit. Severe irritant to the skin of a rabbit. Corrosive to the skin of a rabbit.

## Section 12 – Ecological Information

No data for the product itself.

### Component Data:

#### Component Benzyl Alcohol:

EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative.  
 Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*),  
 Toxicity to Algae: IC50 (72hr) 700 mg/l

#### Component CAS# 69-72-7:

Toxicity to Fish LC50 (*Leuciscus idus* – 96 mg/l. Toxicity to Daphnia magna – 105mg/l, 24 hr. Component Mutagenic Effects: Mutagenic for bacteria and/or yeast. Developmental toxicity: Classified reproductive system toxin/female, development toxin possible.

#### Component CAS# 80-05-7:

Acute Ecotoxicity tests LC50 (fathead minnow) 96 hr = 4.6 mg/l. LC50 (daphnia magna) 48 hr = 3.9 mg/l. LC50 (algae) 96 hr = 2.73 mg/l.

#### Component Nonyl Phenol:

Ecotoxicity: Daphnia EC50: 0.14-0.44 mg/l, 48 hr. Component is not readily biodegradable, Log Pow: 3-4. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Toxicity LC50 96 hr, toxicity rating is <0.10 ppm – extremely toxic

#### Component CAS# 90-72-2 and CAS# 71074-89-0:

Toxicity: LC50 fish 447.8 mg/l (96 hr). LC50 Crust 28.2 mg/l (48 hr). EC50 alga 34.8 mg/l (96 hr)

## Section 13 – Disposal Considerations

### Waste Disposal Method:

Dispose of material as a hazardous waste according to federal, state, and local regulations.

## Section 14 – Transport Information

### DOT:

UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENETRIAMINE, N-AMINOETHYLPIPERAZINE), 8, PG III,

### IMO/IMDG:

UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENETRIAMINE, N-AMINOETHYLPIPERAZINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

## Section 15 – Regulatory Information

No data for the product itself.

### Component Data:

#### Component CAS# 694-83-7:

Component is on the TSCA list and Canada DSL, EINECS, AICS, ENCS, ECL, SEPA, lists or inventory.

#### Component CAS# 694-83-7, Benzyl Alcohol CAS# 100-51-6, Aliphatic Amines:

WHMIS Trade Secret Registration Number 5096 Grant Date 5/4/2004.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Component Aliphatic Amines:

On TSCA, EINECS, AICS, ENCS, ECL, SEPA lists or inventory.

### Component Benzyl Alcohol:

E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada, EINECS, AICS, ENCS, ECL, SEPA, lists or inventory.

### Component CAS# 69-72-7:

Component is on the Pennsylvania and New Jersey Right To Know lists. Component is on the TSCA and Canada DSL lists.

### Component CAS# 111-40-0:

On TSCS List, OSHA hazard class – Irritant. Regulatory List: On TSCA, on EINECS, DSL, AICS, ENCS, ECL, SEPA, PICCS.

### Component CAS# 80-05-7:

This component is subject to SARA Section 313 Reporting Requirements. Component is on TSCA EINECS, AICS, ENCS, ECL, SEPA, PICCS and Canada DSL lists.

### Component CAS# 140-31-8:

Component is listed on the TSCA inventory. Component can be found on the following state Right To Know lists: New Jersey, Pennsylvania, Massachusetts. Component contains no California Prop 65 Significant Risk Level: and none of the chemicals in this product are listed. Component is list on the Canadian DSL list, EINECS, AICS, ENCS, ECL, SEPA, PICCS lists.

### Component Nonyl Phenol:

This component is listed on TSCA, EINECS, ACIS, MITI and Canada DSL lists.

### Component CAS# 90-72-2 and 71074-89-0

EEC symbol – Harmful, harmful if swallowed (R22) Irritating to eyes and skin (R36/38). Component is on the Canada DSL, TSCA, EINECS, AICS, ENCS, ECL, SEPA, PICCS lists.

## Section 16 – Other Information

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**Revision Date: 11/23/2021**

## Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

**Product Name:** Con-Patch II **PART C**  
**Product Codes:** Series No. 8145-10  
**Recommended Use:** Filler/Patch  
**Sold By:** Gabriel First Corp.  
**Street Address:** PO Box 191  
**City, State, Zip:** East Rochester, NY 14445-0191  
**Telephone:** 585-381-7000  
**Emergency Phone:** 800-424-9300  
**Date Revised:** 11/23/2021  
**Chemical Name or Class:** Sand

## Section 2 – Hazards Identification

### Hazard Overview

#### GHS Classification:

Carcinogenicity: Category 1  
 Specific target organ toxicity following repeated exposure: Category 1  
 Specific target organ toxicity (single exposure): Category 3

### GHS Label Elements and Precautionary Statements:

#### Label Elements:



#### Hazard Statements:

**Danger:** May cause cancer.  
**Danger:** Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system).  
**Warning:** May cause respiratory irritation.  
**Precautionary Statements:**

P102 Keep out of reach of children.  
 P103 Read label before use.  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P264 Wash hands thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
**Response:** P308 + P313 IF exposed or concerned: Get medical advice/attention.  
 P314 Get medical advice/attention if you feel unwell.  
 P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
**Storage:** P405 Store locked up.  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
**Disposal:** P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

### HMIS Hazard Classification

**Health: 2      Flammability: 0      Reactivity: 0      Personal Protective Equipment: E**

### Potential Health Effects

**Eyes:** May cause reddening of the eyes or eye irritation from airborne particles.  
**Skin:** None known  
**Ingestion:** None known  
**Inhalation:** Prolonged exposure to respirable crystalline quartz may cause delayed lung injury (silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure in some applications such as sand blasting.

### Health Hazards (Acute and Chronic):

May cause delayed silicosis or rapid silicosis in some occupations such as sandblasting, silicosis is a form of a disabling pulmonary fibrosis which can be progressive and could lead to death. Inhalation may lead to lung scarring and massive fibrosis which could be accompanied by right heart enlargement, heart failure, or pulmonary failure, smoking aggravates the effects of exposure.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Medical Conditions Generally Aggravated By Exposure:

Respiratory conditions or other allergic ailments can be aggravated by exposure.

**Carcinogenicity:** OSHA: No NTP: Yes IARC: Yes

### Additional Carcinogenicity Information:

IARC has determined that crystalline silica inhaled in the form of quartz is carcinogenic to humans (group 1- carcinogenic to humans). The NTP classifies respirable crystalline silica as reasonably anticipated to be a carcinogen.

## Section 3 – Composition/Information on Ingredients

Ingredient	CAS No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Silicon Dioxide	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3	100

### Section 2 Notes:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

Follow OSHA hazard communication rule 29CFR sections 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, and state and local community Right to Know laws. We recommend that smoking be prohibited in areas where respirators must be used.

## Section 4 – First Aid Measures

<b>Eyes:</b>	Flush eyes with water for at least fifteen minutes and consult a physician if conditions warrant.
<b>Skin:</b>	Skin contact will normally cause no health risks.
<b>Ingestion:</b>	If ingested, consult a physician.
<b>Inhalation:</b>	Remove victim to fresh air and administer oxygen if necessary.
<b>Notes to Physicians or First Aid Providers:</b>	

## Section 5 – Firefighting Measures

<b>Flammable Limits In Air, (% By Volume):</b>	<b>Upper:</b> Not available. <b>Lower:</b> Not available.
<b>Flash Point° F:</b> N/A <b>Method Used:</b> N/A	
<b>Extinguishing Media:</b>	Other.
<b>Special Fire Fighting Procedures:</b>	Crystalline Silica is neither a fire nor an explosion hazard.
<b>Unusual Fire And Explosion Hazards:</b>	None known.

## Section 6 – Accidental Release Measures

<b>Steps To Be Taken In Case Material Is Released Or Spilled:</b>	Wear respirator and use dustless handling equipment to clean up large spills, place in suitable containers for disposal. Flush area with water after pickup of material.
---	--

## Section 7 – Handling and Storage

<b>Precautions To Be Taken In Handling and Storage:</b>	Store in cool dry place. Properly label all containers and reseal all partially used containers. Avoid creating any dust when working with this material.
<b>Other Precautions:</b>	Avoid breathing dust generated from the material. Observe conditions of good general hygiene and safe working practices. Provide training for your employees relating to occupational exposure to quartz dust. See ASTM Standard E1132-86 Standard Practice For Health Requirements Relating to Exposure To Quartz Dust. If better than 500 X PEL use a self-contained breathing apparatus. If sandblasting, use any type CE supplied air respirator with full face piece or hood.
<b>Safety Phrases</b>	S22 Do not breathe dust. S25 Avoid contact with eyes. S38 In case of insufficient ventilation wear suitable respiratory equipment. S39 Wear eye/face protection.

## Section 8 – Exposure Controls/Personal Protection

<b>Respiratory Protection:</b>	Use a NIOSH approved respirator as required to prevent over-exposure to quartz dust. Provide sufficient exhaust to keep exposure levels below the ACGIH PEL.
<b>Ventilation:</b>	Use exhaust sufficient to maintain airborne particulates below the ACGIH PEL limits established.
<b>Protective Gloves:</b>	N/A
<b>Eye Protection:</b>	Splash goggles or glasses with side shields.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Other Protective Clothing or Equipment:** Provide any equipment necessary to prevent the inhalation of quartz dust.

**Work Hygienic Practices:** Observe good general hygienic practices.

See Section Three for occupational exposure limit values.

### Section 9 – Physical and Chemical Properties

<b>Appearance and Odor:</b>	White of tan sand granular crushed or ground- no odor
<b>Boiling Point or Range ° F:</b>	N/A
<b>Vapor Density (Air = 1):</b>	N/A
<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	2.6
<b>Evaporation Rate:</b>	N/A
<b>Solubility in Water:</b>	Insoluble in water
<b>Odor Threshold:</b>	N/A
<b>pH:</b>	N/A
<b>Melting Point/Freezing Point:</b>	N/A
<b>Vapor Pressure:</b>	N/A
<b>Auto-ignition Temperature:</b>	N/A
<b>Partition Coefficient: n-Octanol/Water:</b>	N/A
<b>Decomposition Temperature:</b>	N/A

### Section 10 – Stability and Reactivity

<b>Stability:</b>	Stable.
<b>Conditions to Avoid (Stability):</b>	Contact with powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, oxygen trifluoride.
<b>Incompatibility (Material to Avoid):</b>	Can react vigorously with strong oxidizing agents- see conditions to avoid.
<b>Hazardous Decomposition or By-Products:</b>	Silica will dissolve in hydrochloric acid to form a corrosive gas- Silicon Tetrafluoride.
<b>Hazardous Polymerization:</b>	Will not occur.

### Section 11 – Toxicological Information

**Silicon dioxide:** Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute. Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

### Section 12 – Ecological Information

**Silicon Dioxide:** There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

### Section 13 – Disposal Considerations

**Waste Disposal Method:** Dispose of the material in a waste disposal site in accordance with local, state, and federal law.

### Section 14 – Transport Information

<b>DOT:</b>	Not Regulated
<b>IMO/IMDG</b>	Not regulated

### Section 15 – Regulatory Information

**Silicon Dioxide:**

Risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation.

Safety Phrases: S 22 – Do Not Breathe Dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment

**Crystalline Silica (Silicon Dioxide)** is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and Community Right To Know Act list as a hazardous substance.

**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

**Crystalline Silica (Silicon Dioxide)** is on the Canada DSL – WHMIS Classification D2A

**Crystalline Silica** is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with Registry Number 9212-5667 and the Philippines Inventory of Chemicals and Chemical Substances list.

**Section 16 – Other Information**

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**Revision Date: 11/23/2021**